


www.coachman.co.uk

Coachman Specifications 2010



Coachman Caravan Company Limited
 Amsterdam Road
 Sutton Fields Industrial Estate
 Hull HU7 0XF

Telephone: 01482 839737
Aftercare Telephone: 01482 877405
Fax: 01482 878143
Email: sales@coachman.co.uk

Distinction Quality Style 

This brochure has been designed to provide you with basic information prior to making a purchase decision. Please refer to your dealer for additional information before you buy.

Coachman Caravan Company Limited reserves the right to alter technical specifications, prices and model ranges as materials and conditions demand and can accept no responsibility for discrepancies between these and subsequent models. Household items illustrated in the brochure (e.g. fruit and personal effects) have been used to enhance photography and are not supplied with the caravan. Limitations in the printing process may mean colours are not truly represented.

It should be noted that distributors and dealers are not the agents of Coachman Caravan Company Limited and therefore are not authorised to bind the Company by any specific or implied undertaking or representation.

Please note: Touring caravans are designated by the model year. The model year runs from the 1st September to the 31st August: for example a 2010 year model would have been despatched by the manufacturer no earlier than the 15th August, 2009.

All Coachman models have been certified by the National Caravan Council for compliance with stringent European Standards, British Legislation and industry set Codes of Practice, specifically relating to health and safety issues. The approval process covers the testing and inspection of critical areas of the product from fire safety, weights and dimensions to gas, electrics and ventilation. Every Coachman caravan carries the "NCC Approved Caravan" badge. The NCC also conducts unannounced inspections at the Coachman factory to ensure continued compliance.


NCC Approval gives you peace of mind that your caravan is legal and safe.

The tow cars used in this brochure are for illustration purposes only.

As the owner of a Coachman caravan, you will be automatically entitled to join our Owners' Club. For more information about the Club, please contact: The Membership Officer, Coachman Owners' Club, 2 Braemar Rise, South Hiendley, Barnsley, South Yorkshire, S72 9DJ or visit their website: www.coachmanclub.co.uk

Photography: www.markkennett.com and www.glennblackburn.co.uk.
 Designed and produced by: www.bluestormdesign.co.uk



Distinction Quality Style 



Technical Specifications 2010

Model	650/4	655/6
Number of Berths	4	6
Interior Length	6190 mm/20' 4"	6190 mm/20' 4"
Shipping Length	7965 mm/26' 2"	7965 mm/26' 2"
Overall Width	2260 mm/7' 5"	2260 mm/7' 5"
Overall Height (inc T.V Aerial)	2632 mm/8' 8"	2632 mm/8' 8"
Maximum Headroom	1955 mm/6' 5"	1955 mm/6' 5"
Interior Width	2110 mm/6' 11"	2110 mm/6' 11"
Wheel Rim	5.5J x 14	5.5J x 14
Tyre Size	175/65 R14 86	175/65 R14 86
Tyre Pressure (at quoted MTPLM)	44 psi/3 bar	44 psi/3 bar
Bed Sizes	2 x Single	1 x Single
Option 1	1800 mm x 720 mm (6' 3" x 2' 4") 1680 mm x 720 mm (5' 6" x 2' 4") 1 x Double 1830 mm x 1380 mm (6' 0" x 4' 6")	1920 mm x 720 mm (6' 3" x 2' 4") 1 x Single 1885 mm x 720 mm (6' 2" x 2' 4") 2 x Single 1780 mm x 700 mm (5' 10" x 2' 4") 2 x Single Bunks 1700 mm x 610 mm (5' 7" x 2' 0")
Bed Sizes	1 x Double	1 x Double
Option 2	2030 mm x 1220 mm (6' 8" x 4' 0") 1 x Double 1830 mm x 1380 mm (6' 0" x 4' 6")	2030 mm x 1420 mm (6' 8" x 4' 8") 1 x Double 1980 mm x 1300 mm (6' 6" x 4' 3") 2 x Single Bunks 1700 mm x 610 mm (5' 7" x 2' 0")
M.T.P.L.M	1800 kg/35.4 cwt	1860 kg/36.6 cwt
Mass in Running Order	1566 kg/30.8 cwt	1616 kg/31.8 cwt
Essential Habitation Equipment	84 kg/1.7 cwt	84 kg/1.7 cwt
Personal Payload	140 kg/2.8 cwt	160 kg/3.1 cwt
Options Payload	10 kg/0.2 cwt	0 kg/0 cwt
Total / Maximum User Payload	234 kg/4.6 cwt	244 kg/4.8 cwt
Empty Nose Weight	74 kg/1.5 cwt	49 kg/1 cwt
Maximum Hitch Weight	100 kg/1.9 cwt	100 kg/1.9 cwt
Awning Size	1058 cm	1058 cm



Technical Specifications 2010

Model	460/2	470/2	520/4	535/4	545/4	560/4
Number of Berths	2	2	4	4	4	4
Interior Length	4858 mm/15' 11"	5000 mm/16' 5"	5514 mm/18' 1"	5500 mm/18' 1"	5800 mm/19' 0"	5800 mm/19' 0"
Shipping Length	6633 mm/21' 9"	6775 mm/22' 3"	7289 mm/23' 11"	7275 mm/23' 10"	7575 mm/24' 10"	7575 mm/24' 10"
Overall Width	2260 mm/7' 5"	2260 mm/7' 5"	2260 mm/7' 5"	2260 mm/7' 5"	2260 mm/7' 5"	2260 mm/7' 5"
Overall Height (inc T.V Aerial)	2672 mm/8' 9"	2672 mm/8' 9"	2672 mm/8' 9"	2672 mm/8' 9"	2672 mm/8' 9"	2672 mm/8' 9"
Maximum Headroom	1955 mm/6' 5"	1955 mm/6' 5"	1955 mm/6' 5"	1955 mm/6' 5"	1955 mm/6' 5"	1955 mm/6' 5"
Interior Width	2110 mm/6' 11"	2110 mm/6' 11"	2110 mm/6' 11"	2110 mm/6' 11"	2110 mm/6' 11"	2110 mm/6' 11"
Wheel Rim	5.5J x 14	5.5J x 14	6.0J x 15	6.0J x 15	6.0J x 15	6.0J x 15
Tyre Size	185 R14 102	185 R14 102	195/70 R15 104	195/70 R15 104	195/70 R15 104	195/70 R15 104
Tyre Pressure (at quoted MTPLM)	65 psi / 4.5 bar	65 psi / 4.5 bar	65 psi / 4.5 bar	65 psi / 4.5 bar	65 psi / 4.5 bar	65 psi / 4.5 bar
Bed Sizes	2 x Single	2 x Single	2 x Single	2 x Single	2 x Single	1 x Single
Option 1	1900 mm x 720 mm (6' 3" x 2' 4")	1900 mm x 720 mm (6' 3" x 2' 4")	1900 mm x 720 mm (6' 3" x 2' 4") 1 x Single 1830 mm x 720 mm (6' 0" x 2' 4") 1 x Single Bunk 1760 mm x 610 mm (5' 9" x 2' 0")	1690 mm x 720 mm (5' 6" x 2' 4") 1 x Double 1960 mm x 1420 mm (6' 5" x 4' 8")	1550 mm x 720 mm (5' 1" x 2' 4") 1 x Double 1830 mm x 1380 mm (6' 0" x 4' 6")	1560 mm x 720 mm (5' 1" x 2' 4") 1 x Single 1650 mm x 720 mm (5' 5" x 2' 4") 1 x Double 1900 mm x 1320 mm (6' 3" x 4' 4")
Bed Sizes	1 x Double	1 x Double	1 x Double	1 x Double	1 x Double	1 x Double
Option 2	2030 mm x 1420 mm (6' 8" x 4' 8")	2030 mm x 1420 mm (6' 8" x 4' 8")	2030 mm x 1420 mm (6' 8" x 4' 8") 1 x Single 1830 mm x 720 mm (6' 0" x 2' 4") 1 x Single Bunk 1760 mm x 610 mm (5' 9" x 2' 0")	2030 mm x 1200 mm (6' 8" x 3' 11") 1 x Double 1960 mm x 1420 mm (6' 5" x 4' 8")	2030 mm x 1100 mm (6' 8" x 3' 7") 1 x Double 1830 mm x 1380 mm (6' 0" x 4' 6")	2030 mm x 1100 mm (6' 8" x 3' 7") 1 x Double 1900 mm x 1320 mm (6' 3" x 4' 4")
M.T.P.L.M	1410 kg/27.8 cwt	1420 kg/28 cwt	1575 kg/31 cwt	1560 kg/30.7 cwt	1610 kg/31.7 cwt	1630 kg/32.1 cwt
Mass in Running Order	1250 kg/24.6 cwt	1259 kg/24.8 cwt	1389 kg/27.3 cwt	1366 kg/26.9 cwt	1413 kg/27.8 cwt	1433 kg/28.2 cwt
Essential Habitation Equipment	48 kg/0.9 cwt	48 kg/0.9 cwt	48 kg/0.9 cwt	48 kg/0.9 cwt	48 kg/0.9 cwt	48 kg/0.9 cwt
Personal Payload	107 kg/2.1 cwt	108 kg/2.1 cwt	108 kg/2.1 cwt	133 kg/2.6 cwt	136 kg/2.7 cwt	136 kg/2.7 cwt
Options Payload	5 kg/0.1 cwt	5 kg/0.1 cwt	5 kg/0.1 cwt	13 kg/0.3 cwt	13 kg/0.3 cwt	13 kg/0.3 cwt
Total / Maximum User Payload	160 kg/3.1 cwt	161 kg/3.2 cwt	186 kg/3.7 cwt	194 kg/3.8 cwt	197 kg/3.9 cwt	197 kg/3.9 cwt
Empty Nose Weight	46 kg/0.9 cwt	53 kg/1.1 cwt	56 kg/1.1 cwt	60 kg/1.2 cwt	54 kg/1.1 cwt	52 kg/1.0 cwt
Maximum Hitch Weight	100 kg/1.9 cwt	100 kg/1.9 cwt	100 kg/1.9 cwt	100 kg/1.9 cwt	100 kg/1.9 cwt	100 kg/1.9 cwt
Awning Size	935 cm	945 cm	995 cm	992 cm	1030 cm	1030 cm



Technical Specifications 2010

Model	460/2	520/4	535/4	545/4
Number of Berths	2	4	4	4
Interior Length	4858 mm/15' 11"	5514 mm/18' 1"	5500 mm/18' 1"	5800 mm/19' 0"
Shipping Length	6633 mm/21' 9"	7289 mm/23' 11"	7275 mm/23' 10"	7575 mm/24' 10"
Overall Width	2260 mm/7' 5"	2260 mm/7' 5"	2260 mm/7' 5"	2260 mm/7' 5"
Overall Height (inc T.V Aerial)	2672 mm/8' 9"	2672 mm/8' 9"	2672 mm/8' 9"	2672 mm/8' 9"
Maximum Headroom	1955 mm/6' 5"	1955 mm/6' 5"	1955 mm/6' 5"	1955 mm/6' 5"
Interior Width	2110 mm/6' 11"	2110 mm/6' 11"	2110 mm/6' 11"	2110 mm/6' 11"
Wheel Rim	5.5J x 14	6.0J x 15	6.0J x 15	6.0J x 15
Tyre Size	185 R14 102	195/70 R15 104	195/70 R15 104	195/70 R15 104
Tyre Pressure (at quoted MTPLM)	65 psi/4.5 bar	65 psi/4.5 bar	65 psi/4.5 bar	65 psi/4.5 bar
Bed Sizes	2 x Single	2 x Single	2 x Single	2 x Single
Option 1	1900 mm x 720 mm (6' 3" x 2' 4")	1900 mm x 720 mm (6' 3" x 2' 4") 1 x Double 1830 mm x 720 mm (6' 0" x 2' 4") 1 x Single Bunk 1760 mm x 610 mm (5' 9" x 2' 0")	1690 mm x 720 mm (5' 6" x 2' 4") 1 x Double 1960 mm x 1420 mm (6' 5" x 4' 8")	1550 mm x 720 mm (5' 1" x 2' 4") 1 x Double 1830 mm x 1380 mm (6' 0" x 4' 6")
Bed Sizes	1 x Double	1 x Double	1 x Double	1 x Double
Option 2	2030 mm x 1420 mm (6' 8" x 4' 8")	2030 mm x 1420 mm (6' 8" x 4' 8") 1 x Single 1830 mm x 720 mm (6' 0" x 2' 4") 1 x Single Bunk 1760 mm x 610 mm (5' 9" x 2' 0")	2030 mm x 1200 mm (6' 8" x 3' 11") 1 x Double 1960 mm x 1420 mm (6' 5" x 4' 8")	2030 mm x 1100 mm (6' 8" x 3' 7") 1 x Double 1830 mm x 1380 mm (6' 0" x 4' 6")
M.T.P.L.M	1420 kg/28 cwt	1585 kg/31.2 cwt	1565 kg/30.8 cwt	1620 kg/31.9 cwt
Mass in Running Order	1265 kg/24.9 cwt	1404 kg/27.6 cwt	1376 kg/27.1 cwt	1428 kg/28.1 cwt
Essential Habitation Equipment	48 kg/0.9 cwt	48 kg/0.9 cwt	48 kg/0.9 cwt	48 kg/0.9 cwt
Personal Payload	107 kg/2.1 cwt	133 kg/2.6 cwt	136 kg/2.7 cwt	136 kg/2.7 cwt
Options Payload	0 kg/0 cwt	0 kg/0 cwt	8 kg/0.2 cwt	8 kg/0.2 cwt
Total / Maximum User Payload	155 kg/3.1 cwt	181 kg/3.6 cwt	189 kg/3.7 cwt	192 kg/3.8 cwt
Empty Nose Weight	45 kg/0.9 cwt	55 kg/1.1 cwt	59 kg/1.2 cwt	54 kg/1.1 cwt
Maximum Hitch Weight	100 kg/1.9 cwt	100 kg/1.9 cwt	100 kg/1.9 cwt	100 kg/1.9 cwt
Awning Size	935 cm	995 cm	992 cm	1030 cm



Technical Specifications 2010

Model	380/2	450/2	520/4	535/4	550/5	560/4	570/6	640/6
Number of Berths	2	2	4	4	5	4	6	6
Interior Length	3973 mm/13' 0"	4675 mm/15' 4"	5428 mm/17' 10"	5500 mm/18' 1"	5620 mm/18' 5"	5800 mm/19' 0"	5800 mm/19' 0"	6171 mm/20' 3"
Shipping Length	5728 mm/18' 10"	6430 mm/21' 1"	7183 mm/23' 7"	7255 mm/23' 10"	7375 mm/24' 2"	7555 mm/24' 9"	7555 mm/24' 9"	7926 mm/26' 0"
Overall Width	2260 mm/7' 5"	2260 mm/7' 5"	2260 mm/7' 5"	2260 mm/7' 5"	2260 mm/7' 5"	2260 mm/7' 5"	2260 mm/7' 5"	2260 mm/7' 5"
Overall Height (inc T.V Aerial)	2600 mm/8' 6"	2600 mm/8' 6"	2600 mm/8' 6"	2600 mm/8' 6"	2600 mm/8' 6"	2600 mm/8' 6"	2600 mm/8' 6"	2575 mm/8' 5"
Maximum Headroom	1911 mm/6' 3"	1911 mm/6' 3"	1911 mm/6' 3"	1911 mm/6' 3"	1911 mm/6' 3"	1911 mm/6' 3"	1911 mm/6' 3"	1911 mm/6' 3"
Interior Width	2110 mm/6' 11"	2110 mm/6' 11"	2110 mm/6' 11"	2110 mm/6' 11"	2110 mm/6' 11"	2110 mm/6' 11"	2110 mm/6' 11"	2110 mm/6' 11"
Wheel Rim	5.5J x 14	5.5J x 14	5.5J x 14	5.5J x 14	6.0J x 15	6.0J x 15	6.0J x 15	5.5J x 14
Tyre Size	175 R14 99	185 R14 102	185 R14 102	185 R14 102	195/70 R15 104	195/70 R15 104	195/70 R15 104	175/65 R14 86
Tyre Pressure (at quoted MTPLM)	65 psi / 4.5 bar	65 psi / 4.5 bar	65 psi / 4.5 bar	65 psi / 4.5 bar	65 psi / 4.5 bar	65 psi / 4.5 bar	65 psi / 4.5 bar	44 psi / 3 bar
Bed Sizes	2 x Single	2 x Single	2 x Single	1 x Single	2 x Single	1 x Single	1 x Single	2 x Single
Option 1	1850 mm x 720 mm (6' 1" x 2' 4")	1850 mm x 720 mm (6' 1" x 2' 4")	1850 mm x 720 mm (6' 1" x 2' 4") 1 x Single 1830 mm x 720 mm (6' 0" x 2' 4") 1 x Single Bunk 1760 mm x 610 mm (5' 9" x 2' 0")	1680 mm x 720 mm (5' 6" x 2' 4") 1 x Single 1640 mm x 720 mm (5' 5" x 2' 4") 1 x Double 1955 mm x 1420 mm (6' 5" x 4' 8")	1850 mm x 720 mm (6' 1" x 2' 4") 1 x Double 2030 mm x 1370 mm (6' 8" x 4' 6") 1 x Single Bunk 1950 mm x 610 mm (6' 5" x 2' 0")	1560 mm x 720 mm (5' 1" x 2' 4") 1 x Single 1640 mm x 720 mm (5' 4" x 2' 4") 1 x Double 1900 mm x 1320 mm (6' 3" x 4' 4")	1770 mm x 720 mm (5' 10" x 2' 4") 1 x Single 1800 mm x 720 mm (5' 11" x 2' 4") 1 x Single (rear) 1830 mm x 720 mm (6' 0" x 2' 4") 1 x Single Bunk 1770 mm x 610 mm (5' 10" x 2' 0") 2 x Single Bunks 1750 mm x 610 mm (5' 9" x 2' 0")	1830 mm x 720 mm (6' 0" x 2' 4") 1 x Single Bunk 1830 mm x 720 mm (6' 0" x 2' 4") 1 x Single Bunk 1760 mm x 610 mm (5' 9" x 2' 0") 2 x Single Bunks 1750 mm x 610 mm (5' 9" x 2' 0")
Bed Sizes	1 x Double	1 x Double	1 x Double	1 x Double	1 x Double	1 x Double	1 x Double	1 x Double
Option 2	2030 mm x 1380 mm (6' 8" x 4' 6")	2030 mm x 1380 mm (6' 8" x 4' 6")	2030 mm x 1380 mm (6' 8" x 4' 6") 1 x Single 1830 mm x 720 mm (6' 0" x 2' 4") 1 x Single Bunk 1760 mm x 610 mm (5' 9" x 2' 0")	2030 mm x 1200 mm (6' 8" x 3' 11") 1 x Double 1955 mm x 1420 mm (6' 5" x 4' 8")	2030 mm x 1380 mm (6' 8" x 4' 6") 1 x Double 2030 mm x 1370 mm (6' 8" x 4' 6") 1 x Single Bunk 1950 mm x 610 mm (6' 5" x 2' 0")	2030 mm x 1090 mm (6' 8" x 3' 7") 1 x Double 1900 mm x 1320 mm (6' 3" x 4' 4")	2030 mm x 1300 mm (6' 8" x 4' 3") 1 x Double 1830 mm x 720 mm (6' 0" x 2' 4") 1 x Single Bunk 1770 mm x 610 mm (5' 10" x 2' 0") 2 x Single Bunks 1750 mm x 610 mm (5' 9" x 2' 0")	2030 mm x 1380 mm (6' 8" x 4' 6") 1 x Single Bunk 1830 mm x 720 mm (6' 0" x 2' 4") 1 x Single Bunk 1760 mm x 610 mm (5' 9" x 2' 0") 2 x Single Bunks 1750 mm x 610 mm (5' 9" x 2' 0")
M.T.P.L.M	1195 kg/23.5 cwt	1335 kg/26.3 cwt	1500 kg/29.5 cwt	1470 kg/28.9 cwt	1580 kg/31.1 cwt	1560 kg/30.7 cwt	1600 kg/31.5 cwt	1700 kg/33.5 cwt
Mass in Running Order	1042 kg/20.5 cwt	1175 kg/23.1 cwt	1313 kg/25.8 cwt	1282 kg/25.2 cwt	1381 kg/27.2 cwt	1369 kg/26.9 cwt	1394 kg/27.4 cwt	1485 kg/29.2 cwt
Essential Habitation Equipment	47 kg/0.9 cwt	47 kg/0.9 cwt	47 kg/0.9 cwt	47 kg/0.9 cwt	47 kg/0.9 cwt	47 kg/0.9 cwt	47 kg/0.9 cwt	47 kg/0.9 cwt
Personal Payload	98 kg/1.9 cwt	105 kg/2.1 cwt	132 kg/2.6 cwt	133 kg/2.6 cwt	144 kg/2.8 cwt	136 kg/2.7 cwt	156 kg/3.1 cwt	160 kg/3.1 cwt
Options Payload	8 kg/0.2 cwt	8 kg/0.2 cwt	8 kg/0.2 cwt	8 kg/0.2 cwt	8 kg/0.2 cwt	8 kg/0.2 cwt	8 kg/0.2 cwt	8 kg/0.2 cwt
Total / Maximum User Payload	153 kg/3 cwt	160 kg/3.1 cwt	187 kg/3.7 cwt	188 kg/3.7 cwt	199 kg/3.9 cwt	191 kg/3.8 cwt	206 kg/4.1 cwt	215 kg/4.2 cwt
Empty Nose Weight	48 kg/0.9 cwt	42 kg/0.8 cwt	45 kg/0.9 cwt	64 kg/1.3 cwt	56 kg/1.1 cwt	54 kg/1.1 cwt	55 kg/1.1 cwt	56 kg/1.1 cwt
Maximum Hitch Weight	100 kg/1.9 cwt	100 kg/1.9 cwt	100 kg/1.9 cwt	100 kg/1.9 cwt	100 kg/1.9 cwt	100 kg/1.9 cwt	100 kg/1.9 cwt	100 kg/1.9 cwt
Awning Size	825 cm	890 cm	965 cm	980 cm	992 cm	1010 cm	1010 cm	1050 cm